

CW-3020



CW-3020PV-CNC



TJG-3030



TJG-3030DV-CNC



| 規格 SPECIFICATION | CW-3020PV-CNC | TJG-3030DV-CNC |
|---------------------------|--|---|
| 量測範圍 MEASURING RANGE | 300 x 200 x 100 mm(X,Y,Z) | 300 x 300 x 200 mm(X,Y,Z) |
| 解析讀數 RESOLUTION | 0.001 mm Scales | 0.0005mm in 3 Axes (三軸) |
| 量測軟體 SOFTWARE | IK5000-VED-CNC-AF | IK5000-VED-CNC-AF |
| 影像系統 VISION | Color CCD + Zoom | Color CCD + Zoom |
| 放大倍率 ZOOM | 10X ... 100X (Option 20X ~ 200X) | 10X ... 100X (Option 20X ~ 200X) |
| 表面燈源 SURFACE LIGHT | White LED (Option of Coaxial LED) | White LED (Option of Coaxial LED) |
| 輪廓底光 CONTOUR LIGHT | Green LED | Green LED |
| 量測精度 ACCURACY | U1= 2 + L/200 um | U1= 3 + L/200 um ; U2= 5 + L/150 um |
| 單點重複精度 REPEATABILITY | 0.002 um | 0.002 mm |
| 傳動方式 TRANSMISSION | Linear Guideway + Rolling Drive Nut 無牙螺桿 + 線性滑軌 | Linear Guideway + Rolling Drive Nut 無牙螺桿 + 線性滑軌 |
| 操作方式 OPERATION | CNC Programmable 程序控制 | CNC Programmable 程序控制 |
| 驅動方式 DRIVE | Servo Motors + Joystick | Servo Motors + Joystick |
| 鑄鐵平臺 CAST IRON | | |
| 工件限高 DEMO-PARTS HEIGHT | 140 mm Max. | 200 mm |
| 工作限重 DEMO-PARTS WEIGHT | 12 kgs Max. | 12 kgs |
| 外型尺寸 DIMENSION | 890 x 820 x 1090 mm (Including Base Stand) | 770 x 1000 x 930 mm |
| 外型尺寸 - 包括週邊 DIMENSION | 1300 x 950 x 1850 mm (Including Deluxe Table) | 1400 x 1000 x 930 mm (Including Deluxe Table) |
| 機器重量 MACHINE WEIGHT | 382 kgs | 360 kgs |
| 電腦硬體 HARDWARE | PC + 24" Monitor + WIN-PRO | PC + 24" Monitor + WIN-PRO |
| 選購配備 OPTION | Programmable Light-Control or Auto-Zoom, Probe, Laser 程式控制調光或倍率調整, 測頭, 雷射 | |