

Value+

Optical Power Meters

- Help to inspect optical fibre capabilities
- Able to calculate relative power loss
- Locate the fault and trouble shooting
- Linear indicators (mW) and non-linear indicators (dBm) display in one screen
- Large display for easy reading
- Able to connect to SC, FC and ST type plug (with optional adaptors)
- High Performance Meter for precise measurement
- With Visible Laser Beam, to have visual fault checking of optical fibre (Some Models)
- Compact and Trendy Look
- Easy to Use and Carry
- Auto Power Off to save battery power
- Eco Friendly by using Rechargeable Batteries (Some Models)



Optical Power Meters



Basic Functions	VT22D	VT22E	VT22F	VT23D	VT23E	VT23F
Wavelength (nm)		850, 980, 1300, 1310, 1490, 1550, 1620				
Detector type		InGaAs				
Power measurement range		-70 ~ 6 dBm				
Power measurement accuracy		±0.3 (5%)				
Resolution		0.01				
Optical output connector		2.5mm ST, SC, FC				
Red visible laser		✓	✓		✓	✓
Laser Output		> 10mW	> 1mW		> 10mW	> 1mW
Low Battery Display	✓	✓	✓	✓	✓	✓
Auto Power Off	✓	✓	✓	✓	✓	✓
Powered by		1.5V (AA) x 3		3.7V Rechargeable Battery (14500) x 3		

* All information provided are subject to change without prior notice.

Futronix Co.

Rm 609 Lee On Industrial Building,
70 Hung To Road, Kwun Tong, Kowloon,
HONG KONG

Tel : (852) 3580 7725

Fax : (852) 3753 4800

e-mail : info@futronix-hk.com



Your Distributor :