



Photo : DGA404



Cordless Angle Grinder
DGA404 / DGA454 / DGA504
 100mm (4") 115mm (4-1/2") 125mm (5")

Satisfy Professional's Needs



BL
MOTOR

BRUSHLESS



Excellent Performance
as powerful as AC model

Accessory Dust collecting wheel guard



Part No.
196845-3
196846-1

Part No. vary by country or area



Photo : DGA504

Battery



- BL1850: 18V 5.0Ah
- BL1840: 18V 4.0Ah
- BL1830: 18V 3.0Ah
- BL1820: 18V 2.0Ah
- BL1815N: 18V 1.5Ah

Charger

DC18RC



Charging time (3.0Ah)
22minutes

Two Port Multi
Fast Charger
DC18RD



Four Port Multi Charger
DC18SF

Charging time (3.0Ah)
1 to 2 batteries : 60minutes
3 to 4 batteries : 120minutes



DC18SD
Charging time (3.0Ah)
60minutes



DC18SE (Automotive)
Charging time (3.0Ah)
60minutes



Cordless Angle Grinder

DGA404 100mm (4") / **DGA454** 115mm (4-1/2") / **DGA504** 125mm (5")



Soft Start

Carrying Case



	DGA404	DGA454	DGA504
Wheel diameter	100mm (4")	115mm (4-1/2")	125mm (5")
No load speed (rpm)	8,500	8,500	8,500
Dimensions (L x W x H)	362x117x140mm (14-1/4"x4-5/8"x5-1/2")	362x130x145mm (14-1/4"x5-1/8"x5-3/4")	362x140x145mm (14-1/4"x5-1/2"x5-3/4")
Net weight	BL1830: 2.4kg (5.3lbs)	BL1830: 2.5kg (5.5lbs)	BL1830: 2.5kg (5.6lbs)

Standard Equipment :

Fast Charger, Battery Cartridge, Depressed Center Grinding Wheel, Lock Nut Wrench, Side Grip

weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BE-BA



Easy-to-hold grip design with rubber for anti-skid



Battery fuel gauge
Also warns that Anti-restart function and Current limiter have been activated.

Anti-restart function
prevents accidental startup for safety even if the machine is plugged to power source with the lock-on switch on.



Handles heavy load with Excellent Cooling Function!
Protects component parts!
Realizes Maximum Efficiency!

BL MOTOR

18V LITHIUM-ION

XPT
EXTREME PROTECTION TECHNOLOGY

For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.


Slide switch

Removable Dust Cover

The First in the Industry!
Equipped with Automatic Speed Control!

Automatically changes the cutting speed according to load condition for an optimum operation


The above rank is within 14.4V & 18V class of Cordless Angle Grinders, and is based on our research in July 2014.



High torque mode : 1 solid green LED




Photo : DGA404
The standard equipment for the tool may vary by country.




at depth of 20mm

Efficiency of concrete cutting

Test conditions: Cut concrete continuously at depths of 20mm, and measured the time required to cut across a 600mm wide.



Test conditions: Cut concrete continuously at depths of 10mm, and measured the time required to cut across a 600mm wide.



Note: 1. The test results depend to a great extent on the hardness of materials, etc.
2. The numbers in the bar graphs are relative values when the capacity of Makita 115mm predecessor model is indexed at 100. When it is impossible to measure the result, the best performing model is indexed at 100 instead.