

## SPECIFICATIONS

# PXI-8512

## 1- or 2-Port, High-Speed, Flexible Data Rate PXI CAN Interface Module

This document lists specifications for the PXI-8512 1-port and 2-port CAN interface module.

## Definitions

---

*Warranted* specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

*Characteristics* describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- *Typical* specifications describe the performance met by a majority of models.
- *Nominal* specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are *Typical* unless otherwise noted.

## Conditions

---

Specifications are typical at 0 °C to 55 °C unless otherwise noted.

## Power Requirements

---

+5 VDC (±5%)	640 mA
+3.3 VDC (±5%)	940 mA

---

## Physical

---

### Dimensions and Weight

Dimensions	10.67 cm x 16.76 cm (4.2 in. x 6.6 in.)
------------	---

---

## Weight

1 port	98 g (3.5 oz)
2 port	102 g (3.6 oz)

## RTSI/Front Panel Sync Connectors

Trigger lines	7 input/output
Clock lines	1 input/output
I/O compatibility	TTL
Power-on state	Input (High-Z)
Response	Rising edge triggers

## Physical Characteristics

CAN Physical Layer	High-Speed CAN, Flexible Data Rate
Transceiver <sup>1</sup>	NXP TJA1041 or TJA1043
Max baud rate <sup>2</sup>	1 Mbps
Min baud rate	40 kbps
CAN_H, CAN_L bus lines voltage	-27 VDC to +40 VDC

## Environmental

Operating temperature	0 °C to 55 °C
Storage temperature	-20 °C to 70 °C (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.)
Operating humidity	10% to 90% RH, noncondensing
Storage humidity	5% to 95% RH, noncondensing (Tested in accordance with IEC-60068-2-56.)
Maximum altitude	2000 m
Pollution Degree (IEC 60664)	2

Indoor use only.

<sup>1</sup> PXI-8512 revision G and later use the TJA1043 transceiver; previous hardware revisions use the TJA1041 transceiver. To identify your hardware revision, refer to the 19xxxx<rev>-4xL text on the green label in the top left corner on the secondary side of the board; <rev> indicates the hardware revision.

<sup>2</sup> The TJA1043 transceiver is CiA certified for baud rates up to 5 Mbit/s in the CAN FD fast phase while speeds up to 8 Mbit/s are possible experimentally. NI-XNET will provide a warning when a transceiver is used at higher baud rates than certified for. As newly CiA certified transceivers with higher baud rates are released, NI will continue to update the hardware with newer revisions.

# Shock

---

Operating shock	30 g peak, half-sine, 11 ms pulse (Tested in accordance with IEC-60068-2-27. Test profile developed in accordance with MIL-PRF-28800F.)
-----------------	---

---

# Random Vibration

---

Operating	5 Hz to 500 Hz, 0.3 $g_{rms}$
Nonoperating	5 Hz to 500 Hz, 2.4 $g_{rms}$ (Tested in accordance with IEC-60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.)

---

# Safety

---

## Isolation Voltages

---

Port-to-port ground	
Withstand	500 $V_{rms}$ verified by a 5 s dielectric withstand test
Continuous	60 VDC, Measurement Category I
Port-to-earth ground	
Withstand	500 $V_{rms}$ verified by a 5 s dielectric withstand test
Continuous	60 VDC, Measurement Category I

---



**Note** This isolation is intended to prevent ground loops.

Measurement Category I is for measurement performed on circuits not directly connected to the electrical distribution system referred to as MAINS voltage. MAINS is a hazardous live electrical supply system that powers equipment. This category is for measurements of voltages from specially protected secondary circuits. Such voltage measurements include signal levels, special equipment, limited-energy parts of equipment, circuits powered by regulated low-voltage sources, and electronics.



**Caution** Do not connect the PXI-8512 to signals or use for measurements within Measurement Categories II, III, or IV.



**Attention** Ne connectez pas le PXI-8512 à des signaux et ne l'utilisez pas pour effectuer des mesures dans les catégories de mesure II, III ou IV.



**Note** Measurement Categories CAT I and CAT O (Other) are equivalent. These test and measurement circuits are not intended for direct connection to the MAINS building installations of Measurement Categories CAT II, CAT III, and CAT IV.

## Safety Standards

This product is designed to meet the requirements of the following standards of safety for information technology equipment:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1



**Note** For UL and other safety certifications, refer to the product label or the *Product Certifications and Declarations* section.

## Electromagnetic Compatibility

---

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326 (IEC 61326): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- AS/NZS CISPR 11: Group 1, Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



**Note** For EMC declarations and certifications, and additional information, refer to the *Product Certifications and Declarations* section.



**Note** For EMC compliance, operate this product according to the documentation.



**Notice** When operating this product, use shielded cables and accessories.

## CE Compliance

---

This product meets the essential requirements of applicable European Directives, as follows:

- 2014/35/EU; Low-Voltage Directive (safety)
- 2014/30/EU; Electromagnetic Compatibility Directive (EMC)

# Product Certifications and Declarations

---

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit [ni.com/certification](https://ni.com/certification), search by model number or product line, and click the appropriate link in the Certification column.

## Environmental Management

---

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the *Minimize Our Environmental Impact* web page at [ni.com/environment](https://ni.com/environment). This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

## Waste Electrical and Electronic Equipment (WEEE)



**EU Customers** At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit [ni.com/environment/weee](https://ni.com/environment/weee).

## 电子信息产品污染控制管理办法（中国 RoHS）



**中国客户** National Instruments 符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于 National Instruments 中国 RoHS 合规性信息，请登录 [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china)。(For information about China RoHS compliance, go to [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china).)

Information is subject to change without notice. Refer to the *NI Trademarks and Logo Guidelines* at [ni.com/trademarks](http://ni.com/trademarks) for information on NI trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering NI products/technology, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your media, or the *National Instruments Patent Notice* at [ni.com/patents](http://ni.com/patents). You can find information about end-user license agreements (EULAs) and third-party legal notices in the `readme` file for your NI product. Refer to the *Export Compliance Information* at [ni.com/legal/export-compliance](http://ni.com/legal/export-compliance) for the NI global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. NI MAKES NO EXPRESS OR IMPLIED WARRANTIES AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN AND SHALL NOT BE LIABLE FOR ANY ERRORS. U.S. Government Customers: The data contained in this manual was developed at private expense and is subject to the applicable limited rights and restricted data rights as set forth in FAR 52.227-14, DFAR 252.227-7014, and DFAR 252.227-7015.

© 2012—2018 National Instruments. All rights reserved.

377688A-01 December 11, 2018